

PARIS-90-3C/ PARIS-90-3C VISION




Main features

- Cast iron door, interior and grate.
- Regulation of the primary and secondary air inlet regulations.
- Triple Combustion System.
- Includes fan with 2 speeds switch.
- Silent. Possibility of total disconnection of the turbine.
- Regulation of the front air by means of a blade, with possibility to close it completely and increase the flow rate for channeling.
- With channeling possibility (includes 2 micro-perforated outlets to channel air up to 3 meters, includes channeling collars).
- Includes roast grill removable, rotating and adjustable in several heights.
- Includes adjustable legs in height.
- Frame included as standard.
- Glove and spray paint included.

Optional elements:

- KIT-AIR-2: External air kit. To become airtight

Colores disponibles:



Datos técnicos

	Potencia cedida al aire (kW) máx.-mín.: 16 - 5,4		Potencia (kW) nom.: 13
	Volumen calefactable (m³): 325		Rendimiento %: 81
	Consumo (kg/h): 3,9		Diámetro de salida de humos (cm): 20
	Ventilación forzada (m³/h): 1x335		Canalizable (diámetro y número de salidas): 3m. x 2 (120)
	Peso (Kg): 161		Tamaño máximo troncos (cm): 75
	Medidas boca útil: 780x306x286		Material exterior: Acero y Fundición
	Material cámara combustión: Fundición		

Sistemas

	Sistema Cristal Limpio		Silenciosa
	Sistema Triple Combustión		

Certificaciones



15aB-VG
DIN Plus
l.BimSchV2

Given the continuous improvement of our products and the refinement of our manufacturing process, the dimensions, aesthetics of the product and technical characteristics are subject to possible variations without prior notice from our company. ©Bronpi Calefacción, S.L. reserves all rights to the images appearing in this document. The partial or total reproduction or dissemination of the photographs and text is prohibited. Both the brand and the symbols are distinctive features that are the exclusive property of the company. Violators will be prosecuted in accordance with the law.